

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Name : ANTI-CORROSION UNDERBODY COATING  
Trade name : COBRA UNDERBODY SHIELD

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses**

Main use category : Professional use  
Use of the substance/mixture : The product is intended for professional use

**1.3. Details of the supplier of the safety data sheet**

NOVOL Sp. z o.o.  
Żabikowska 7/9  
62-052 KOMORNIKI, Poland  
Poland  
T +48618109800, F +48618109809  
[sekretariat@novol.com](mailto:sekretariat@novol.com), [www.novol.com](http://www.novol.com)  
E-mail address of competent person responsible for the SDS : [dokumentacja@novol.com](mailto:dokumentacja@novol.com)

**1.4. Emergency telephone number**

Emergency number : 112

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 1 H318  
Skin sensitisation, Category 1 H317

Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

Signal word (CLP) :

Danger

Contains :

butan-1-ol; n-butanol

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P261 - Avoid breathing vapours, spray.  
P271 - Use only outdoors or in a well-ventilated area.

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call doctor if you feel unwell.

EUH-statements : EUH205 - Contains epoxy constituents. May produce an allergic reaction.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\geq 700 < 1100$ )	CAS-No.: 25068-38-6 EC-No.: ---- EC Index-No.: --- REACH-no: --	< 30	Skin Sens. 1, H317
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 106-42-3 EC-No.: 203-396-5 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	< 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315
butan-1-ol; n-butanol substance with national workplace exposure limit(s) (GB)	CAS-No.: 71-36-3 EC-No.: 200-751-6 EC Index-No.: 603-004-00-6 REACH-no: 01-2119484630-38	< 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
aluminium powder (stabilised) substance with national workplace exposure limit(s) (GB) (Note T)	CAS-No.: 7429-90-5 EC-No.: 231-072-3 EC Index-No.: 013-002-00-1 REACH-no: 01-2119529243-45	0 – 0.4	Water-react. 2, H261 Flam. Sol. 1, H228
phthalic anhydride substance with national workplace exposure limit(s) (GB)	CAS-No.: 85-44-9 EC-No.: 201-607-5 EC Index-No.: 607-009-00-4 REACH-no: 01-2119457017-41	< 0.1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317
ethylbenzene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	< 0.03	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 2, H373 Asp. Tox. 1, H304

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : General information. Refer to section 11.  
First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.  
Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry.  
Symptoms/effects after eye contact : May cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO<sub>2</sub>, alcohol-resistant foam or waterspray.  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Protective equipment : Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.

##### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. See Section 8.

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

### 6.3. Methods and material for containment and cleaning up

For containment : Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

### 6.4. Reference to other sections

Disposal considerations. See Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

xylene (106-42-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup> o-,m-,p- or mixed isomers
	100 ppm o-,m-,p- or mixed isomers

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>xylene (106-42-3)</b>	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>butan-1-ol; n-butanol (71-36-3)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butan-1-ol
WEL STEL (OEL STEL)	154 mg/m <sup>3</sup> 50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>aluminium powder (stabilised) (7429-90-5)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Aluminium
WEL TWA (OEL TWA)	2 mg/m <sup>3</sup> alkyl compounds 2 mg/m <sup>3</sup> salts, soluble 10 mg/m <sup>3</sup> metal, inhalable dust 4 mg/m <sup>3</sup> metal, respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>ethylbenzene (100-41-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Ethylbenzene
IOEL TWA	442 mg/m <sup>3</sup> 100 ppm
IOEL STEL	884 mg/m <sup>3</sup> 200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethylbenzene
WEL TWA (OEL TWA)	441 mg/m <sup>3</sup> 100 ppm
WEL STEL (OEL STEL)	552 mg/m <sup>3</sup> 125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>ethylbenzene (100-41-4)</b>	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>phthalic anhydride (85-44-9)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Phthalic anhydride
Remark	Respiratory sensitizer; skin sensitizer. (Year of adoption 2010)
Regulatory reference	SCOEL Recommendations
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Phthalic anhydride
WEL TWA (OEL TWA)	4 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	12 mg/m <sup>3</sup>
Remark	Sen (Capable of causing occupational asthma)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### Recommended monitoring procedures

<b>Monitoring methods</b>	
Monitoring methods	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

### DNEL and PNEC

<b>xylene (106-42-3)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	289 mg/m <sup>3</sup>
Acute - local effects, inhalation	289 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>
Long-term - local effects, inhalation	221 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	174 mg/m <sup>3</sup>
Acute - local effects, inhalation	174 mg/m <sup>3</sup>
Long-term - systemic effects,oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.8 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC aqua (intermittent, marine water)	0.001 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	12.46 mg/kg dwt

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>xylene (106-42-3)</b>	
PNEC sediment (marine water)	12.46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2.31 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	6.58 mg/l
<b>butan-1-ol; n-butanol (71-36-3)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - local effects, inhalation	310 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	3.125 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	55.357 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	3.125 mg/kg bodyweight/day
Long-term - local effects, inhalation	55 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.082 mg/l
PNEC aqua (marine water)	0.0082 mg/l
PNEC aqua (intermittent, freshwater)	2.25 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.178 mg/kg dwt
PNEC sediment (marine water)	0.0178 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.015 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2476 mg/l

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Personal protection equipment

#### Personal protective equipment symbol(s):



### Eye and face protection

#### Eye protection:

Safety glasses

### Skin protection

#### Skin and body protection:

Wear suitable protective clothing

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Viton® II	6 (> 480 minutes)	0,7 mm		EN 374-3, EN ISO 374-1
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0,4 mm		EN 374-3

### Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Silver grey. Black.
Odour	: characteristic.
Odour threshold	: 0.9 – 9 mg/m <sup>3</sup> Xylene
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive properties	: No data available.
Lower explosion limit	: 1.1 vol % Xylene
Upper explosion limit	: 8 vol % Xylene
Flash point	: 26 °C
Auto-ignition temperature	: 440 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 256.41 – 1307.19 mm <sup>2</sup> /s
Viscosity, dynamic	: 400 – 2000 mPa·s
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 9 hPa
Vapour pressure at 50°C	: Not available
Density	: 1.53 – 1.56 g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Keep away from sources of ignition. Prevent build-up of electrostatic charges (e.g. by grounding). Protect from sunlight. Avoid high temperatures.

#### 10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon monoxide. Other toxic gases.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met).

<b>xylene (106-42-3)</b>	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat	27124 mg/l
<b>butan-1-ol; n-butanol (71-36-3)</b>	
LD50 oral rat	≈ 2292 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	3430 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	8000 ppm Source: ECHA
<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight &gt;= 700 &lt; 1100) (25068-38-6)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg Source: CHEMIDPLUS
<b>aluminium powder (stabilised) (7429-90-5)</b>	
LD50 oral rat	> 15900 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>ethylbenzene (100-41-4)</b>	
LD50 oral rat	≈ 3500 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 20000 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	4000 ppm
<b>phthalic anhydride (85-44-9)</b>	
LD50 oral rat	1530 mg/kg Source: ECHA
LD50 dermal rabbit	> 3160 mg/kg Source: HSDB
LC50 Inhalation - Rat	> 2.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 2.14 mg/l Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified.
<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>phthalic anhydride (85-44-9)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	3570 mg/kg bodyweight Animal: mouse, Animal sex: male
NOAEL (chronic, oral, animal/female, 2 years)	1785 mg/kg bodyweight Animal: mouse, Animal sex: female
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
<b>aluminium powder (stabilised) (7429-90-5)</b>	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
<b>butan-1-ol; n-butanol (71-36-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>phthalic anhydride (85-44-9)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
<b>xylene (106-42-3)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
<b>butan-1-ol; n-butanol (71-36-3)</b>	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat
<b>aluminium powder (stabilised) (7429-90-5)</b>	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (subchronic, oral, animal/male, 90 days)	1034 mg/kg bodyweight Animal: dog, Animal sex: male, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>aluminium powder (stabilised) (7429-90-5)</b>	
NOAEL (subchronic, oral, animal/female, 90 days)	1087 mg/kg bodyweight Animal: dog, Animal sex: female, Guideline: OECD Guideline 409 (Repeated Dose 90-Day Oral Toxicity Study in Non-Rodents)
<b>ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
<b>phthalic anhydride (85-44-9)</b>	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
<b>COBRA UNDERBODY SHIELD</b>	
Viscosity, kinematic	256.41 – 1307.19 mm <sup>2</sup> /s
<b>butan-1-ol; n-butanol (71-36-3)</b>	
Viscosity, kinematic	3.641 mm <sup>2</sup> /s
<b>aluminium powder (stabilised) (7429-90-5)</b>	
Viscosity, kinematic	Not applicable

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>xylene (106-42-3)</b>	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
<b>butan-1-ol; n-butanol (71-36-3)</b>	
LC50 - Fish [1]	1376 mg/l Source: ECHA
EC50 - Crustacea [1]	1983 mg/l Source: ECHA
EC50 96h - Algae [1]	225 mg/l Source: ECHA
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\geq 700 &lt; 1100</math>) (25068-38-6)</b>	
LC50 - Fish [1]	10 – 30 mg/l Source: National Institute of Technology and Evaluation
EC50 - Crustacea [1]	10 – 23 mg/l Test organisms (species): Daphnia magna
<b>aluminium powder (stabilised) (7429-90-5)</b>	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
<b>ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
<b>phthalic anhydride (85-44-9)</b>	
LC50 - Fish [1]	> 99 mg/l Source: ECHA
EC50 - Crustacea [1]	> 640 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 640 mg/l Test organisms (species):
EC50 72h - Algae [1]	68 mg/l Source: ECHA
NOEC (chronic)	16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	10 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '60 d'

### 12.2. Persistence and degradability

<b>COBRA UNDERBODY SHIELD</b>	
Persistence and degradability	Not rapidly degradable
<b>xylene (106-42-3)</b>	
Persistence and degradability	Not rapidly degradable
<b>butan-1-ol; n-butanol (71-36-3)</b>	
Persistence and degradability	Not rapidly degradable
<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\geq 700 &lt; 1100</math>) (25068-38-6)</b>	
Persistence and degradability	Not rapidly degradable
<b>aluminium powder (stabilised) (7429-90-5)</b>	
Persistence and degradability	Not rapidly degradable

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>ethylbenzene (100-41-4)</b>	
Persistence and degradability	Not rapidly degradable
<b>phthalic anhydride (85-44-9)</b>	
Persistence and degradability	Not rapidly degradable

### 12.3. Bioaccumulative potential

<b>butan-1-ol; n-butanol (71-36-3)</b>	
Partition coefficient n-octanol/water (Log Pow)	1 Source: ECHA
<b>reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <math>\geq 700 &lt; 1100</math>) (25068-38-6)</b>	
Partition coefficient n-octanol/water (Log Pow)	2821 Source: National Institute of Technology and Evaluation
<b>ethylbenzene (100-41-4)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB
<b>phthalic anhydride (85-44-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.6 Source: HSDB

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Do not discharge into drains.  
Product/Packaging disposal recommendations : This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.  
Additional information : Flammable vapours may accumulate in the container.  
European List of Waste (LoW, EC 2000/532) : 08 01 11\* - waste paint and varnish containing organic solvents or other dangerous substances  
15 01 10\* - packaging containing residues of or contaminated by dangerous substances  
European List of Waste (LoW, EC 2000/532)

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

# COBRA UNDERBODY SHIELD

## Safety Data Sheet


SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA
<b>14.1. UN number or ID number</b>		
UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>		
PAINT	PAINT	Paint
<b>Transport document description</b>		
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III, MARINE POLLUTANT (26°C c.c.)	UN 1263 Paint, 3, III
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		
<b>14.4. Packing group</b>		
III	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: No
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Limited quantities (ADR) : 5I  
Special packing provisions (ADR) : PP1  
Mixed packing provisions (ADR) : MP19  
Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V12  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3Y

#### Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955  
Limited quantities (IMDG) : 5 L  
Special packing provisions (IMDG) : PP1  
Stowage category (IMDG) : A

#### Air transport

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

###### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

###### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

###### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

###### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

###### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

###### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

###### Explosives Precursors Regulation (EU 2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

###### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

#### Indication of changes:

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources : ECHA (European Chemicals Agency).

Training advice : Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2

# COBRA UNDERBODY SHIELD

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.